

ESE[®]

Super Blower

Series E /BYE



Stock Code	Model	Specification		Power (W)	Phase (PH)	Voltage (V)	Frequency (Hz)	Wind Pressure (Pa)	Blow Rate (m ³ /min)	Rotation Speed (rpm)
		(Inch)	(mm)							
881102006	BYE6332	2-1/2	70	250	1	230	50	2510	19	2800
881102013	BYE7132	3	80	550	3	415		1700	15	
881102020	BYE7152	4	100	1100	3	415		2510	19	

ESE super blower is characterized with the merits of low noise, large air volume, high wind pressure, small body, light weight and easy installation etc. It is widely used for ventilation in various places for conduit wind conveying, conveying of low density service media. And it is preferred matching product for plastic machinery, printing machinery, textile machinery, kitchen utensils machinery, diesel combustion machinery and diesel oil gasification furnace.

Stock Code	Model	Specification		Power (W)	Phase (PH)	Voltage (V)	Frequency (Hz)	Wind Pressure (Pa)	Blow Rate (m ³ /min)	Rotation Speed (rpm)
		(Inch)	(mm)							
881102006	E1B	2-1/2	65	250	1	230	50	1050	8.5	2800
881102007	E1TB	2-1/2	65	250	3	415		1050	8.5	
881102011	E4D	3	75	550	1	230		2000	11.5	
881102013	E4TD	3	75	550	3	415		2000	11.5	
881102015	E8TD	5	120	2200	3	415		2800	28.0	
881102019	E9D	4	95	1100	1	230		2300	21.6	
881102020	E9TD	4	95	1100	3	415		2300	21.6	

***Product's specification may subject to change without further notice.
 ***Actual product may slightly differ from pictures shown.